1   What is claimed is:

2

3   1.   A method for determining therapeutic resonant frequencies of electromagnetic radiation

4   for influencing a target genomic material, the genomic material surrounded by a medium,

5   comprising:

6   providing a frequency-emitting device;

7   determining a velocity of the electromagnetic radiation through the medium surrounding

8   the genomic material;

9   determining a wavelength of the genomic material;

10   determining a first resonant frequency of the genomic material in one electromagnetic

11   frequency range by dividing the velocity of the electromagnetic radiation through the

12   surrounding medium by the wavelength of the genomic material;

13   shifting the first resonant frequency by a factor of a power of two to at least one of a

14   group of resonant frequencies in at least one other electromagnetic frequency range;

15   programming the frequency-emitting device to emit the at least one of a group of

16   resonant frequencies in the at least one other electromagnetic frequency range; and

17   selectively influencing the target genomic material with the at least one of a group of

18   resonant frequencies in the at least one other electromagnetic frequency range when the

19   frequency-emitting device emits the at least one of a group of resonant frequencies in the at least

20   one other electromagnetic frequency range into the medium surrounding the target genomic

21   material.

22

23   2.   The method of claim 1, the genomic material comprising a plurality of spaced apart base

24   pairs, wherein determining the wavelength of the genomic material comprises determining the

27

1 number of base pairs in the genomic material, measuring the spacing between adjacent base

2 pairs, and multiplying the number of base pairs in the genomic material by the spacing between

3 adjacent base pairs.

4

5 3.   The method of claim 1, the genomic material comprising a plurality of base pairs spaced

6 apart by an average spacing, the average spacing comprising a known value, wherein

7 determining the wavelength of the genomic material comprises determining the number of base

8 pairs in the genomic material and multiplying the number of base pairs in the genomic material

9 by the known value for the average spacing between base pairs.

10

11 4.   The method of claim 1, wherein the medium surrounding the genomic material is in-vivo

12 tissue having a unique electrical permittivity, wherein determining the velocity of the

13 electromagnetic radiation through the medium surrounding the genomic material comprises

14 relating the unique electrical permittivity of in-vivo tissue to the velocity, wherein velocity $= 1 /$

15 $\sqrt{(\varepsilon_0 \mu_0)}$, where ε_0 is electrical permittivity, and μ_0 is magnetic permeability.

16

17 5.   The method of claim 4, further comprising the step of determining a refractive index of

18 the electromagnetic radiation through the in-vivo tissue by dividing the speed of light in a

19 vacuum by the speed of light in in-vivo tissue, wherein dividing one therapeutic resonant

20 frequency determined for the genomic material surrounded by air by the refractive index for in-

21 vivo tissue yields one of the therapeutic resonant frequencies for the genomic material

22 surrounded by in-vivo tissue.

23

1 6. The method of claim 1, further comprising the steps of:

2   multiplying the at least one of a group of resonant frequencies in at least one other

3 electromagnetic frequency range by a positive integer to determine harmonic frequencies,

4   dividing the at least one of a group of resonant frequencies in at least one other

5 electromagnetic frequency range by a positive integer to determine subharmonic frequencies,

6   programming the frequency-emitting device to emit the harmonic and subharmonic

7 frequencies, and

8   selectively influencing the target genomic material with the at least one of a group of

9 resonant frequencies in at least one other electromagnetic frequency range and the harmonic and

10 subharmonic frequencies when the frequency-emitting device emits the at least one of a group of

11 resonant frequencies in at least one other electromagnetic frequency range and the harmonic and

12 subharmonic frequencies into the medium surrounding the target genomic material.

13

14 7. The method of claim 1, wherein selectively influencing the target genomic material

15 comprises debilitating the target genomic material.

16

17 8. The method of claim 1, wherein selectively influencing the target genomic material

18 comprises stimulating the target genomic material.

19

20 9. The method of claim 1, wherein selectively influencing the target genomic material with

21 the at least one of a group of resonant frequencies in the at least one other electromagnetic

22 frequency range comprises selectively influencing genomic material in humans.

23

1   10.   The method of claim 1, wherein selectively influencing the target genomic material with

2   the at least one of a group of resonant frequencies in the at least one other electromagnetic

3   frequency range comprises selectively influencing genomic material in animals.

4

5   11.   The method of claim 1, wherein selectively influencing the target genomic material with

6   the at least one of a group of resonant frequencies in the at least one other electromagnetic

7   frequency range comprises selectively influencing genomic material in agricultural settings.

8

9   12.   The method of claim 1, wherein selectively influencing the target genomic material with

10   the at least one of a group of resonant frequencies in the at least one other electromagnetic

11   frequency range comprises selectively influencing genomic material in water systems.

12

13   13.   The method of claim 1, wherein selectively influencing the target genomic material with

14   the at least one of a group of resonant frequencies in the at least one other electromagnetic

15   frequency range comprises selectively influencing genomic material in food processing systems.

16

17   14.   The method of claim 1, wherein the medium surrounding the genomic material is in-vivo

18   tissue, further comprising the steps of:

19   determining for the genomic material in a medium of air the first resonant frequency in

20   one electromagnetic frequency range and the at least one of a group of resonant frequencies in at

21   least one other electromagnetic frequency range, and

22   multiplying the first resonant frequency in one electromagnetic frequency range and the

23   at least one of a group of resonant frequencies in at least one other electromagnetic frequency

1 range determined for the genomic material in a medium of air by the square root of two to yield

2 corresponding resonant frequencies for the genomic material surrounded by in-vivo tissue.

3

4 15. A method for determining therapeutic resonant frequencies of electromagnetic radiation

5 for influencing a target genomic material, the genomic material surrounded by a first medium,

6 comprising:

7   providing a frequency-emitting device;

8   determining a velocity of the electromagnetic radiation through the first medium;

9   determining a wavelength of the genomic material, the genomic material comprising a

10 plurality of base pairs spaced apart by an average spacing, the average spacing comprising a

11 known value, wherein determining the wavelength of the genomic material comprises

12 determining the number of base pairs in the genomic material and multiplying the number of

13 base pairs in the genomic material by the known value for the average spacing between base

14 pairs;

15   determining a first resonant frequency of the genomic material in one electromagnetic

16 frequency range by dividing the velocity of the electromagnetic radiation through the first

17 medium by the wavelength of the genomic material;

18   shifting the first resonant frequency by a factor of a power of two to at least one of a

19 group of resonant frequencies in at least one other electromagnetic frequency range;

20   multiplying the at least one of a group of resonant frequencies in at least one other

21 electromagnetic frequency range by a positive integer to determine harmonic frequencies;

22   dividing the at least one of a group of resonant frequencies in at least one other

23 electromagnetic frequency range by a positive integer to determine subharmonic frequencies;

1   programming the frequency-emitting device to emit the at least one of a group of

2   resonant frequencies in the at least one other electromagnetic frequency range and the harmonic

3   and subharmonic frequencies; and

4   selectively influencing the target genomic material with the at least one of a group of

5   resonant frequencies in the at least one other electromagnetic frequency range and the harmonic

6   and subharmonic frequencies when the frequency-emitting device emits the at least one of a

7   group of resonant frequencies in the at least one other electromagnetic frequency range and the

8   harmonic and subharmonic frequencies into the first medium surrounding the target genomic

9   material.

10

11   16.   The method of claim 15, wherein the genomic material is surrounded by a second

12   medium, further comprising determining resonant frequencies for the genomic material

13   surrounded by the second medium, the second medium having a unique electrical permittivity,

14   further comprising determining the velocity of the electromagnetic radiation through the second

15   medium according to the relationship

16    $$\text{velocity} = 1 / \sqrt{(\varepsilon_0 \, \mu_0)},$$

17   where ε_0 is electrical permittivity, and μ_0 is magnetic permeability, dividing the speed of light in

18   a vacuum by the velocity in the second medium to determine a refractive index of the

19   electromagnetic radiation through the second medium, and dividing the first resonant frequency

20   in one electromagnetic frequency range and the at least one of a group of resonant frequencies in

21   at least one other electromagnetic frequency range determined for the genomic material in the

22   first medium by the refractive index for the second medium.

23

32

1   17.   A method for determining therapeutic resonant frequencies of electromagnetic radiation

2   for influencing atomic and molecular particles, each particle having a mass and surrounded by a

3   medium, comprising:

4   providing a frequency-emitting device;

5   determining a velocity of the electromagnetic radiation through the medium surrounding

6   the particle;

7   determining a wavelength of the particle by dividing Plank's constant by the product of

8   the mass of the particle and the speed of light;

9   determining a first resonant frequency of the particle in one electromagnetic frequency

10   range by dividing the velocity of the electromagnetic radiation through the surrounding medium

11   by the wavelength of the particle;

12   shifting the first resonant frequency by a factor of a power of two to at least one of a

13   group of resonant frequencies in at least one other electromagnetic frequency range;

14   programming the frequency-emitting device to emit the at least one of a group of

15   resonant frequencies in the at least one other electromagnetic frequency range; and

16   selectively influencing the target particle with the at least one of a group of resonant

17   frequencies in the at least one other electromagnetic frequency range when the frequency-

18   emitting device emits the at least one of a group of resonant frequencies in the at least one other

19   electromagnetic frequency range into the medium surrounding the particle.

20

21   18.   The method of claim 17, wherein the medium surrounding the particle is in-vivo tissue

22   having a unique electrical permittivity, wherein determining the velocity of the electromagnetic

23   radiation through the medium surrounding the particle comprises relating the unique electrical

1   permittivity of in-vivo tissue to the velocity, wherein velocity $= 1 / \sqrt{(\varepsilon_0 \mu_0)}$, where ε_0 is

2   electrical permittivity, and μ_0 is magnetic permeability.

3

4   19   The method of claim 18, further comprising the step of determining a refractive index of

5   the electromagnetic radiation through the in-vivo tissue by dividing the speed of light in a

6   vacuum by the speed of light in in-vivo tissue, wherein dividing one therapeutic resonant

7   frequency determined for the particle surrounded by air by the refractive index for in-vivo tissue

8   yields one of the therapeutic resonant frequencies for the particle surrounded by in-vivo tissue.

9

10   20.   The method of claim 17, further comprising the steps of:

11   multiplying the at least one of a group of resonant frequencies in at least one other

12   electromagnetic frequency range by a positive integer to determine harmonic frequencies,

13   dividing the at least one of a group of resonant frequencies in at least one other

14   electromagnetic frequency range by a positive integer to determine subharmonic frequencies,

15   programming the frequency-emitting device to emit the harmonic and subharmonic

16   frequencies, and

17   selectively influencing the target particle with the at least one of a group of resonant

18   frequencies in at least one other electromagnetic frequency range and the harmonic and

19   subharmonic frequencies when the frequency-emitting device emits the at least one of a group of

20   resonant frequencies in at least one other electromagnetic frequency range and the harmonic and

21   subharmonic frequencies into the medium surrounding the particle.

22

1   21.   The method of claim 17, wherein selectively influencing the particle comprises

2   debilitating the particle.

3

4   22.   The method of claim 17, wherein selectively influencing the particle comprises

5   stimulating the particle.

6

7   23.   The method of claim 17, wherein selectively influencing the particle with the at least one

8   of a group of resonant frequencies in the at least one other electromagnetic frequency range

9   comprises selectively influencing the particle in humans.

10

11   24.   The method of claim 17, wherein selectively influencing the particle with the at least one

12   of a group of resonant frequencies in the at least one other electromagnetic frequency range

13   comprises selectively influencing the particle in animals.

14

15   25.   The method of claim 17, wherein selectively influencing the particle with the at least one

16   of a group of resonant frequencies in the at least one other electromagnetic frequency range

17   comprises selectively influencing the particle in agricultural settings.

18

19   26.   The method of claim 17, wherein selectively influencing the particle with the at least one

20   of a group of resonant frequencies in the at least one other electromagnetic frequency range

21   comprises selectively influencing the particle in water systems.

22

1   27.   The method of claim 17, wherein selectively influencing the particle with the at least one

2   of a group of resonant frequencies in the at least one other electromagnetic frequency range

3   comprises selectively influencing the particle in food processing systems.

4

5   28.   A method for determining therapeutic resonant frequencies of electromagnetic radiation

6   for influencing atomic and molecular particles, each particle having a mass and surrounded by a

7   first medium, comprising:

8   providing a frequency-emitting device;

9   determining a velocity of the electromagnetic radiation through the first medium

10   surrounding the particle;

11   determining a wavelength of the particle by dividing Plank's constant by the product of

12   the mass of the particle and the speed of light;

13   determining a first resonant frequency of the particle in one electromagnetic frequency

14   range by dividing the velocity of the electromagnetic radiation through the first medium by the

15   wavelength of the particle;

16   shifting the first resonant frequency by a factor of a power of two to at least one of a

17   group of resonant frequencies in at least one other electromagnetic frequency range;

18   multiplying the at least one of a group of resonant frequencies in at least one other

19   electromagnetic frequency range by a positive integer to determine harmonic frequencies;

20   dividing the at least one of a group of resonant frequencies in at least one other

21   electromagnetic frequency range by a positive integer to determine subharmonic frequencies;

1   programming the frequency-emitting device to emit the at least one of a group of

2   resonant frequencies in the at least one other electromagnetic frequency range and the harmonic

3   and subharmonic frequencies; and

4   selectively influencing the particle with the at least one of a group of resonant frequencies

5   in the at least one other electromagnetic frequency range and the harmonic and subharmonic

6   frequencies when the frequency-emitting device emits the at least one of a group of resonant

7   frequencies in the at least one other electromagnetic frequency range and the harmonic and

8   subharmonic frequencies into the first medium surrounding the particle.

9

10   29.   The method of claim 28, wherein the particle is surrounded by a second medium, further

11   comprising determining resonant frequencies for the particle surrounded by the second medium,

12   the second medium having a unique electrical permittivity, further comprising determining the

13   velocity of the electromagnetic radiation through the second medium according to the

14   relationship

15    $$\text{velocity} = 1 / \sqrt{(\varepsilon_0 \, \mu_0)},$$

16   where ε_0 is electrical permittivity, and μ_0 is magnetic permeability, dividing the speed of light in

17   a vacuum by the velocity in the second medium to determine a refractive index of the

18   electromagnetic radiation through the second medium, and dividing the first resonant frequency

19   in one electromagnetic frequency range and the at least one of a group of resonant frequencies in

20   at least one other electromagnetic frequency range determined for the particle in the first medium

21   by the refractive index for the second medium.

22